

IR543 (61-2658) SET-UP AND OPERATING INSTRUCTIONS

1. Plug the IR543 Command Center into any convenient 120VAC outlet.
2. Set the Housecode dial to the same letter as your X-10 or plug 'n power modules.
3. Set the bank switch on the IR543 for the group of modules you want to control from the IR543's keyboard (1-4 or 5-8).

To control lights and appliances from the IR543's keyboard:

1. To turn a module on or off, press and release the corresponding number button for the Unit Code set on the module, i.e. 1, 2, 3, or 4 (or 5, 6, 7, or 8). Then press the ON button or the OFF button on the IR543's keyboard.
2. To dim or brighten lights connected to Lamp Modules and Wall Switch Modules, turn the module on as in step 1 above. Then press and hold the dim or bright button until the desired brightness level is reached.
3. Press All Lights On to turn on ALL lights connected to Lamp Modules and Wall Switch Modules which are set to the same Housecode as the IR543. Note: this affects ALL 16 Unit Codes (not just 1-4 or 5-8).
4. Press All Units Off to turn off ALL modules (including Appliance Modules) which are set to the same Housecode as the IR543. Note this affects ALL 16 Unit Codes (not just 1-4 or 5-8).

Using the Radio Shack 6-in-1 Remote Control (cat. No. 15-1905):

To set up the Remote Control press the plug 'n power button, then press A, then B, then C followed by 167.

To control plug 'n power modules, press the number button for the appropriate module. Then press one of the buttons labelled in blue, i.e. ON, OFF, Bright or DIM. Or press All Lights On or All Units Off.