

Audio/Video AVR Series UPS

Intelligent, Line-Interactive Power Management System



Model #: HTR07-1U

- ▶ 750VA line-interactive 1U UPS; rackmount ears included
- ▶ 6 outlets; 2 switchable load banks
- ▶ Built-in voltage regulation corrects brownouts and overvoltages over an input range of 83V to 147V
- ▶ Simultaneous communications via SNMPWEBCARD slot, USB and DB9 serial ports
- ▶ Included PowerAlert Software manages an unlimited number of network UPS systems
- ▶ 2-year warranty; \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

DESCRIPTION

Tripp Lite's HTR07-1U AVR Series intelligent, line-interactive UPS system prevents media data loss, equipment freeze-ups, downtime and equipment damage due to power outages, voltage fluctuations and transient surges. Network-grade AC surge suppression protects sensitive A/V components from damage due to transient surges and improves component performance (fuller audio/sharper video) by filtering disruptive EMI/RFI line noise. Requires only one rack space (1U); accessories included for upright tower installation. Large internal batteries provide 24 min. half-load runtime and 7 min. full load runtime. Maintains regulated 120V nominal output without using battery power during brownouts as low as 83V. 750VA/450W power handling capability is compatible with audio/video components and other sensitive electronic applications. Includes 6 UPS-supported outlets with two single-outlet load banks that can be individually controlled via software interface to reboot select equipment on demand or automatically shed less significant loads to extend battery runtime for more critical equipment. Supports simultaneous remote monitoring of UPS and site power conditions via built-in USB and DB9 monitoring ports. Includes PowerAlert UPS monitoring and unattended shutdown software with complete cabling. Built-in accessory slot supports SNMP with optional SNMPWEBCARD adapter. Multi-function audible alarms and set of 5 front panel LEDs provide at-a-glance notification of UPS and line power status. Attractive all-black color scheme. 2-year warranty; \$250,000 Ultimate Lifetime Insurance (USA & Canada only).

KEY BUYING POINTS

- HTR07-1U AVR Series line-interactive UPS offers battery-derived sine wave AC output during power outages, voltage regulation during brownouts and overvoltages, plus network-grade AC surge suppression
- 750VA/450W power handling capability compatible with micro display devices, projectors, PVRs/DVRs, media center PCs, music servers and other sensitive electronic devices
- Maintains regulated 120V nominal output during brownouts as low as 83V and overvoltages as high as 147V
- Large internal batteries offer 24 min. runtime at half load (375VA/225W) and 7 min. runtime at full load (750VA/450W)
- Network-grade AC surge suppression protects sensitive A/V components from damage due to transient surges and improves component performance (fuller audio/sharper video) by filtering disruptive EMI/RFI line noise
- Includes 6 UPS-supported outlets with two single-outlet load banks that can be powered on and off via software interface
- PowerAlert UPS monitoring and unattended shutdown software enables configurable network broadcast messaging, pager and email notification, event logging and running user-defined script commands
- Offers simultaneous monitoring by up to 3 directly connected devices through included USB, DB9 and SNMP* interfaces (*requires optional SNMPWEBCARD), or the monitoring of any number of additional UPS systems over IP with included PowerAlert monitoring software
- Communication ports support messaging of UPS and line power status, including on-battery, low-battery, power restored, AC line voltage, DC battery voltage and remaining battery capacity
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by systematically restarting applications, operating systems and ultimately rebooting completely locked computers by momentarily switching UPS power off and back on again (requires optional WATCHDOGSW)
- Built-in accessory slot supports SNMP with optional SNMPWEBCARD adapter

- Multi-function audible alarms and set of 5 front panel LEDs
- Supports 1U rackmount and upright tower installation
- UPS battery set ships fully assembled and ready for installation; no time-consuming connection of internal batteries by user is necessary
- Attractive all-black color scheme
- 2-year warranty; \$250,000 Ultimate Lifetime Insurance (USA & Canada only)

TYPICAL APPLICATIONS

- Ideal for protection of home theater/media center components and other sensitive electronic equipment, including micro display devices, PVRs/DVRs, media center PC/servers, VoIP telephony systems, home automation/control systems and security equipment

OPTIONS & ACCESSORIES

- SNMP accessories: [SNMPWEBCARD](#), [ENVIROSENSE](#)
- USB Hubs-accessories: [U202-004-R](#), [U205-004-R](#), [U022-010](#)
- Dataline protectors: [DNET1](#), [DTEL2](#), [DCATV](#)
- Circuit Tester: [CT120](#)
- Rack enclosures: [Rack Systems](#)
- Power distribution: [PDU1215](#), [PS7224](#)
- Watchdog software: [WATCHDOGSW](#)
- Extended warranties: 3 Year [WEXT3-500-1500](#), 5 Year [WEXT5-500-1500](#)

PACKAGE INCLUDES

- HTR07-1U AVR Series UPS System
- Mounting hardware
- USB and DB9 cabling
- PowerAlert Software
- Instruction manual with warranty information

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

"HTR07-1U AVR Series line-interactive 1U rack/tower UPS protects connected equipment from blackouts, brownouts, surges and EMI/RFI line noise. Maintains AC output during blackouts and continuously corrects brownouts and overvoltages from 83V to 147V back to usable levels. Supports enhanced monitoring of UPS and line power conditions via built-in USB and DB9 ports, included PowerAlert monitoring software and complete cabling. Includes slot for SNMPWEBCARD accessory. Two single-outlet load management banks offer remote reboot of selected loads via software interface or automated load shedding to extend battery runtime for the most critical loads during blackouts. Supports 1U rackmount and upright tower form factors with included mounting hardware. "

Voltage compatibility: 120 VAC

Frequency compatibility: 60 Hz

OUTPUT

Output volt amp capacity (VA): 750

Output watt capacity (watts): 450

Output nominal voltage: 120VAC sine wave output in AC and battery mode

Output voltage regulation: LINE MODE: Sine wave line voltage 120V (-21% +8%), BATTERY MODE: Sine wave output within 5% of 120VAC

Output frequency regulation: LINE MODE: Passes line frequency of 60Hz +/-10% BATTERY MODE: Inverter output regulated to 60Hz +/-0.5Hz

Outlet quantity / type: 6 x NEMA 5-15R

Customized load management receptacles: "2 single-outlet load banks that support automated load shedding and remote reboot on demand of locked network devices. Configurable via PowerAlert software to automatically switch off optional loads, like monitors, to increase available runtime for servers and other critical devices. "

Overload protection: 15A input breaker

INPUT

Maximum input amps: 7A

Input connection type: NEMA 5-15P

Input cord length: 10 ft., 14 gauge

Recommended electrical service: 15A 120V

BATTERY

Full load runtime: 7 min. (450 watts)

Half load runtime: 24 min. (225 watts)

DC system voltage: 24 VDC

Typical battery lifespan: 3-6 years, depending on usage

Battery recharge rate: 2-4 hours to 90%

Replacement Battery Cartridge: RBC64-1U

VOLTAGE REGULATION

Voltage regulation description: Line-interactive voltage regulation system corrects input voltages between 83 and 147 back to usable 120V nominal levels.

Overvoltage correction: Input voltages between 128V and 147V are reduced by 12%

Brownout correction: Input voltages between 83V and 107V are boosted by 14%

LEDS ALARMS & SWITCHES

Front panel LEDs: 5 front panel LEDs - Green POWER LED, 3 color BATTERY CHARGE LED, 3 color OUTPUT LOAD LEVEL LED, red BATTERY WARNING LED.

Alarms: 3-function audible alarm indicates power failure conditions (4 short beeps every 10 seconds), overload (continuous short beeps) and low battery (continuous tone)

Switches: 2 front panel mounted push-button switches for system enable, self-test and alarm cancel functions

PHYSICAL

Shipping weight (lbs): 34

Shipping weight (kg): 15.4

Unit weight (lbs): 30

Unit weight (kg): 13.6

Unit Dimensions (HWD/in): 1.75 x 17.5 x 16.75

Unit Dimensions (HWD/cm): 4.45 x 44.5 x 42.5

Shipping Dimensions (HWD/in): 6.25 x 23.5 x 22.5

Shipping Dimensions (HWD/cm): 15.9 x 60 x 57.2

Material of construction: Steel

Form factors supported: Supports 1U rackmount installation in 2- or 4-post racks; rackmount flanges are reconfigurable to support upright tower placement

Cooling method: Built-in cooling fan

Battery Access: Battery access door allows hot swap battery replacement without powering connected equipment off

ENVIRONMENTAL

Operating Temperature: +32 to +104 degrees Fahrenheit; 0 to +40 degrees Celsius

Storage Temperature: +5 to +122 degrees Fahrenheit; -15 to +50 degrees Celsius

Relative Humidity: 0 to 95%, non-condensing

Line mode BTU/hr. (Max.): 39.2

Battery mode BTU/hr. (Max.): 133.0

COMMUNICATIONS

Network monitoring port: 2 built-in monitoring ports, 1 USB and 1 DB9. Each supports on battery, low battery, power restored, AC line voltage, DC battery voltage, load percentage, battery charge current, battery capacity, internal UPS temperature and line frequency status message

Software and cabling included: PowerAlert UPS monitoring software for network and stand-alone operating systems; ships with complete USB and DB9 cabling.

SNMP compatibility: Built-in accessory slot accommodates internal SNMP / Web card and other network accessories

WatchDog compatibility: Compatible with Tripp Lite's Watchdog Software to restore operation to locked equipment through soft reboot of application / OS or hard power off/on reboot of connected equipment—ideal for unattended kiosk applications

LINE / BATTERY TRANSFER

Transfer time from line power to battery mode: 2-4 milliseconds

Low voltage transfer to battery power: 83V (resets to line power as line voltage increases to 87V or higher)

High voltage transfer to battery power: 147V (resets to line power as line voltage decreases to 143V or lower)

CERTIFICATIONS

Certifications: Tested to UL1778 (USA), Tested to CSA (Canada), Class A (emissions), NOM (Mexico)

WARRANTY

Product warranty: 2 years

Connected equipment insurance (USA and Canada Only): \$250,000

Optional coverage: 3-year, 5-year, next-day and on-site warranty coverage available for select opportunities

SPECIAL FEATURES

EPO port: EPO (Emergency Power Off) port and cable

TVSS grounding: Back panel grounding point with thumbscrew for dataline surge suppressors and other network accessories requiring a safe grounding point

Cold Start: Yes, inverter can be cold started to enable temporary AC output during a power failure

Appearance: Attractive all-black color scheme

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.