

8 Ch. Plug & Play Network Video **Recorder and IP Camera Kit**

ZIPL84D2

8 Channel NVR with 8 Channel Built-In PoE, 2TB 4 Full HD 1080p Outdoor IR Dome Cameras

ZIPL84B2

8 Channel NVR with 8 Channel Built-In PoE, 2TB 4 Full HD 1080p Outdoor IR Bullet Cameras

ZIPL88D2

8 Channel NVR with 8 Channel Built-In PoE, 2TB 8 Full HD 1080p Outdoor IR Dome Cameras


ZIPL88B2

8 Channel NVR with 8 Channel Built-In PoE, 2TB 8 Full HD 1080p Outdoor IR Bullet Cameras

ZIPL8BD2

8 Channel NVR with 8 Channel Built-In PoE, 2TB

- 4 Full HD 1080p Outdoor IR Dome Cameras,
- 4 Full HD 1080p Outdoor IR Bullet Cameras



NVR Features

EZ Set-Up Wizards: one click wizard guides you to set up essentials of the system in a logical and easy to understand sequence.

- Date/Time Recording method Recording video quality Network Port forwarding
- EZ Camera: quickly discovers and installs IP cameras
- EZ Search: quickly search events from thumbnails

EZ Copy: auto copy what you are playing onto a USB flash drive

- Built-In PoE IEEE 802.3af
- Video Out: 1 HDMI®, 1 VGA
- Plug & play feature with Speco's IP cameras
- Dual network ports for isolating IP camera network and remote network traffic
- · Network video recorder with free Speco DDNS server
- Digital Deterrent® for triggering audio message via motion detection or sensor
- Full HD (1920 x 1080) recording and playback

- Switch between low and high quality stream during simultaneous Continuous + Motion or Continuous + Sensor recording modes for storage optimization
- · Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Remote monitoring / recording / playback / configuration / software upgrades and PTZ control via internet
- · Supports multiple PC based browsers such as Internet Explorer, Google Chrome, Firefox and Safari
- · Network accessible via SpecoTech Multi-Client Software, SecureGuard™ Plus CMS and Speco Player Mobile Viewer
- · IR remote control and mouse included
- PC and MAC® compatible
- · 3 year warranty

Camera Features

• Full HD 1080p

• 3.7mm fixed lens

· Real-time video up to 30fps

• PoE IEEE 802.3af

· Dual streaming

· Weather/vandal resistant

IP66 compliant

· 2 year warranty

Camera Specifications

Image Sensor 1/2.8" 2.1MP CMOS

Resolution......1080p/720p

Minimum Illumination.... 0 lux @F2.0 (IR on) / 0.1 lux @F2.0 (IR off)

S/N Ratio 50dB

Motion Detection...... Yes Day/Night..... IR-cut filter

DNR......2D/3D Automatic

Camera Specifications (continued)

Number of IR LEDs Dome: 12 / Bullet: 24

Bullet: 50' (depending on scene reflection)

Operating & Unit Specifications

Power SupplyPoE or 12VDC (power supply not included) Power Consumption Dome: 500mA (IR on) / Bullet: 360mA (IR on)

Operating Temperature.....-4° F - 122° F

Camera Weights......Dome: 14.40 oz. / Bullet: 15.36 oz.

Camera Dimensions Dome: 4.8" (Dia.) x 2.17" (H) / Bullet: 2.64" (Dia.) x 6.25" (L)

NVR Weight.....4 lbs.

Free Apps with support for view on most smart devices

iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/24/15









speco technologies 8 Ch. Plug & Play Network Video Recorder and IP Camera Kit

Model			ZIPL84D2 / ZIPL84B2 / ZIPL88D2 / ZIPL88B2 / ZIPL8BD2
Video	Max. IP Channels		8
	Input	Resolution	Max. 1920 x 1080
		HDMI®	1 HDMI (1280 x 720, 1920 x 1080)
	Output	VGA	1 VGA (1280 x 720, 1920 x 1080)
	Input	IP Camera (Network)	8
Audio	Output	Local Output (RCA)	1
	Audio Codec		G.711
	Compression		H.264 (baseline, main and high profile)
Recording	Resolution	1080p	240fps
		720p	240fps
	Recording Mode		Continuous / Motion / Sensor / Schedule / Manual / Continuous + Motion / Continuous + Sensor
	Pre-Recording		Max. 20 minutes
	Post Recording		Max. 60 seconds
Playback	Search		EZSearch, Date/Time, Event, Archive, Log
	Multi-Decoding		1, 4, 8
	Playback Speed		x0.25, x0.5, x2, x4, x8, x16, x32, x64
Backup Storage	Media		USB Drive, External HDD, Network
	File Format		BMP, AVI, Proprietary Format
		Large Backup	Yes (max. 24 hours)
		Capacity of 1 HDD	2TB
	HDD	Internal HDDs	1
		Front	1
	USB	Rear	1
User I/F		Input Method	IR, Mouse, Keyboard Controller
Event	Sensor In	IP Camera (Network)	8
		Local Input (Terminal Block)	None
	I ocal Al	arm Output (Terminal Block)	None
	Motion Detection (From IP Camera)		Yes
	LAN (IP Camera, Auto Connection)		8 (802.3af PoE)
	WAN (IP Camera, Remote Access)		10/100Base-T
Network	Protocols		TCP/IP, UDP, DHCP, HTTP, NTP, SMTP, RTSP
	Max. Throughput		20Mbps
	Mobile Viewer		iPad® / iPhone® / Android™
	PC Web Viewer		Internet Explorer, Chrome, Firefox, Safari
Network Access	PC Client		SpecoTech Multi-Client Viewer and SecureGuard™ Plus CMS
			Speco Client for MAC and SecureGuard™ CMS
	MAC Client Permote Setup and Upgrade		
	Remote Setup and Upgrade		Yes
	Digital Deterrent®		Default + up to 8 audio files
	Digital Zoom		Yes
	DLS (Daylight Savings)		Yes
.	S.M.A.R.T		Yes
Features	Internal Beep		Yes
	Multi-Language		Yes PRNO
	Dynamic DNS		Yes (free Speco DDNS)
	Email Notification		Yes
D 0	NTP (Network Time Protocol)		Yes
Power Source	Power Supply Voltage		48VDC, 1.2A
Allowable Operating Temperature			41° F - 104° F
Allowable Storage Temperature			14° F - 122° F
Weight	Unit Weight (Gross Weight)		4 lbs.
Dimensions	Unit Dimensions (W x H x D)		11.7" (W) x 2" (H) x 8.25" (D)

Please note that specifications and unit exterior design are subject to change without notification.