

Electromagnetic Locks

E-941SA-600 600-lb Holding Force, UL Listed

E-941SA-600PQ 600-lb Holding Force, with Bond Sensor, LED, UL Listed

Features:

- ▶ Anodized aluminum housing (US 28).
- ▶ 12 or 24VDC (selectable).
- ▶ No residual magnetism.
- ▶ MOV surge protection.
- ▶ Adjustable mounting bracket.
- ▶ Complete mounting hardware for typical installations.
- ▶ “L” bracket and “Z” brackets available for easy mounting.
- ▶ Detachable faceplate.



E-941SA-600PQ features:

- ▶ Built-in dual-colored status LED and bond sensor to show locking status:

Green	Door is closed and locked
Red	Door not closed and/or locked
Off	Door in use / No power


- ▶ Bond sensor relay: 3A@12VDC.

Specifications:


	E-941SA-600	E-941SA-600PQ
Holding force	600-lb (272kg)	
Operating voltage	12 or 24 VDC ±10%	
Current draw	12VDC	500mA@12VDC
	24VDC	250mA@24VDC
Operating temperature	14°~131° F (-10°~55° C)	
Weight	4-lb 6oz (2kg)	
Bond sensor relay		•
Status LED		•

Dimensions:

Electromagnet



Armature Plate



Also Available from SECO-LARM:

