


The Loop™

Hanger for communications cable support. For CAT 5, 6, 7 cable and fiber optic cable.



TL20 TL25




TL50

TL50 holds up to a 5" diameter bundle of CAT 5 or fiber optic cable!




CATALOG NUMBER	UPC/DCI/NAED MFG #018997	LOOP SIZE	# CAT 5 CABLES	UNIT PKG	STD PKG	DIM A	DIM B	LOAD RATING
TL20	38084	2"	60	100	100	11.375	.652	25
TL25	38085	2-1/2"	100	50	50	12.250	1.500	25
TL2520	22031	2-1/2"	100	20	20	12.250	1.500	25
TL50	38086	5"	300	25	25	22.500	5.000	75
TL20P*	38087	2"	60	100	100	11.375	.652	25
TL25P*	38088	2-1/2"	100	50	50	12.250	1.500	25
TL50P*	38089	5"	300	25	25	22.500	5.000	75

*"P" indicates UV Rated.



FEATURES AND BENEFITS

- Easy to use...cheaper than trays!
- Flexible and non-metallic
- Holds 2" to 5" diameter bundle of CAT 5 or fiber optic cable – without damaging the cable.
- Available with or without UV rating
- Versatile mounting – rotates to any angle!
- TL25 holds the same amount of cable as a J-hook, at half the cost!



Installation Shots

1

2

3

4

Single Hanger

1. Single LOOP mounted parallel to beam.
2. Single LOOP mounted perpendicular to beam.

(TL50 shown)

Multiple Hangers

3. Stacked – perpendicular mounting
4. Stacked – parallel mounting

(TL50 shown)

Note: Listed for use in environmental air handling spaces per 2014 NEC code requirements 300.22(c).

Scan For Video

