

Benefits

- Ideal for home automation systems and as stand alone

Applications

Automated operation of awning windows, hopper windows, casement windows, curtain wall vents, and skylights.

Features

- Short-time duty 20% duty cycle
- 24VDC output compact control panel with up to 4A total drive current
- Controls 1 ventilation group
- Input for external controller (timer)
- Optional connection to rain detectors or wind/rain sensors without any additional modules
- 5-year manufacturer's warranty. Requires reading AFI Install Guide before purchase, and confirmation of project and installation specs by licensed electrical contractor



GVL 8304-K-UL

Part #	Color	Description
30.202.10	Light Grey	Control Panel

Specifications

Supply Voltage	120VAC (-15% / +50%)
Output	24VDC / 4A
Dimensions	172mm W x 151mm H x 95mm D (6¾" x 5⅞" x 3¾")
Ambient Oper Temp	-5 °C to +40 °C (23 °F to 104 °F)
Listing	UL Recognized
Protection class	IP50
Typical switch	SPDT Momentary contact (3 leads + ground)
Colors	Plastic: Light Grey RAL 7035

Accessories

Part #	Description
30.300.90	Rain Detector. IP65. 24VDC
30.301.10	Wind/Rain Sensor. Includes antenna mast mounting.
70.602.17	Programmable Wind/Rain heated sensor

Part #	Description
30.902.20	Thermostat
63.701.29	Control Switch



30.300.90



30.301.10



70.602.17



30.902.20



63.701.29

