



## Outdoor Wireless Security Sensor

### SECURITY SENSORS FROM ECOLINK

Ecolink's water resistant contact sensor is perfect for outdoor gates, out of building door detection, or securing mechanical equipment like A/C units. The sensor offers a 3" magnet gap or an external input to allow for use of an external hardwire switch. The high power and large antenna provide the additional wireless range required for most outdoor applications.



GLOBAL

#### APPLICATION:

Outdoor Security Sensor

# Door and Window Sensors


## FEATURES AT A GLANCE

- 345Mhz, Honeywell/2GIG compatible
- IP 56 rated housing for waterproofing
- External Input for flexible application options
- 3" wide sensor magnet gap
- Ample wireless range for most outdoor applications
- Extreme low and high temperature operating range for all outdoor environments
- Strong and durable plastic housing with mounting bracket design



## FLEXIBLE SENSOR APPLICATION

Normally open or normally closed input options allow for installation with an external hardware switch to provide application flexibility. Protect gates, storage or barn doors, outside A/C units, generators, or storage bins.



## SPECIFICATIONS

### WARRANTY

- 24 Months

### POWER

- 2x AA 1.5V Lithium Cell.  
(Up to 10 years battery life)

### RF SPECIFICATIONS

- 345 MHz  
(Honeywell/2GIG Compatible)
- Supervisory signal interval:  
60 min (approx.)

### DIMENSIONS

- Dimensions Sensor - 2.25" x 4.75" x 1.45"
- Dimensions Magnet - 1.00 x 4.25 x 1.25"

### PACKAGING

- Sensor, Magnet, 2x 1"
- Screws for sensor mount, 2x 1.5"
- Screws for magnet mount
- 2x batteries
- Install manual

### ADDITIONAL SPECIFICATIONS

- Magnet gap: 3" max
- Operating Temp: -40F to 140F
- Operating Humidity: 5-99% RH  
non condensing

### REGULATORY AND CERTIFICATION

- ETL Listed for UL 634 burglar alarm use

