

Preference



decorum series

NEW Frameless Design with Magnetically-Attached Grille

K-W6LCRSd In-Wall 2-way LCRS with Rotating Cross-Axis Waveguide

Specifications:

- 6-1/2" Round **Frameless**
- Frequency Response: 45Hz - 27kHz \pm 3 dB
- Power Handling: 60 watts nom. 120 max.
- Sensitivity: 87dB 1 watt / 1 meter
- Tweeter: 25mm Teton[®]
- Impedance: 8 ohms nominal

Features:

- Unique rotating waveguide for superlative image control
- Woven woofers made from genuine DuPont™ Kevlar[®]
- Industry leading superior clamp-ring mounting system
- High-grade crossovers w/ polyswitch overdrive protection
- High temperature polyimide voice coils
- New linear high-excursion design
- Phase plug for high power handling
- Mounts vertically or horizontally
- Timbre-matched tuning
- Magnetic, frameless, vibration-free, all-weather grille

DuPont™ and Kevlar[®] are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



Dimensions:

- Overall Dimensions: 9" x 15-3/4"
- Cut-Out: 7-15/16" x 14-7/16" x 3-5/8" D

Optional Pre-Construction Bracket



Rev. E

Preference[®]
(775) 355-0405 + Fax: (775) 355-0646
www.preference-audio.com + info@preference-audio.com

View the entire
Preference
Product Line:

