

Outdoor No-Touch Request-to-Exit Sensors

- SD-9163-KSQ** *Slimline, English*
- SD-9163-KS1Q** *Slimline, Spanish*
- SD-9163-KSVQ** *Slimline, English, Manual Override*
- SD-9263-KSQ** *Single-Gang, English*
- SD-9263-KS1Q** *Single-Gang, Spanish*
- SD-9263-KSVQ** *Single-Gang, English, Manual Override*

Features:

- ▶ Weather-resistant (IP65) for outdoor use
- ▶ Clean and simple no-touch operation reduces the risk of cross-contamination
- ▶ Adjustable sensor range up to 7" (18cm)
- ▶ Stainless-steel plate, available in slimline or single-gang
- ▶ 1A relay, adjustable trigger duration 0.5~20 seconds
- ▶ Selectable LED colors (turns from red to green or green to red) to show if the sensor is activated

SD-9163-KSVQ and SD-9263-KSVQ

- ▶ Manual override button functions without electricity in case of power failure

SD-9163-KS1Q and SD-9263-KS1Q

- ▶ Screen printed with "SALIDA" and "SIN TOCAR"

Specifications:

Operating voltage		12~24 VDC
Current draw	Standby	16mA@12VDC / 25mA@24VDC
	Triggered	20mA@12VDC / 32mA@24VDC
Relay type		Form C dry contact, 1A@30VDC
Response time		10mS
Output time		0.5~20 s, toggle
Range		2"~7" (5~18cm)
IP rating		IP65
Operating temperature		-4°~131° F (-20°~55° C)
Dimensions	Slimline	1 1/2"x4 1/2"x1 1/2" (39x115x39 mm)
	Single-gang	2 3/4"x4 1/2"x1 1/2" (70x115x39 mm)
Manual override contact rating		3A@250VAC
<small>(SK-9163-KSVQ and SK-9263-KSVQ only)</small>		



SD-9163-KSQ



SD-9163-KSVQ



SD-9263-KSQ



SD-9263-KSVQ

Also Available from SECO-LARM:



Indoor No-Touch
Sensors



Proximity Card
Readers



Request-to-Exit
Plates

SECO-LARM

16842 Millikan Avenue
Irvine, CA 92606

Tel: 1-949-261-2999

1-800-662-0800

Fax: 1-949-261-7326

Web: www.seco-larm.com

Email: info@seco-larm.com



Copyright © 2011
SECO-LARM U.S.A., Inc.
All rights reserved