SECO-LARM®

1,200-lb Single-Door Electromagnetic Locks

E-941SB-1200 Black, UL Listed

E-941SB-1K2PQ Black, with Bond Sensor and Status LED, UL listed

Features

- Multiple UL listings (see chart below) •
- 12/24VDC Selectable
- MOV Surge protection •
- Anodized aluminum housing with black finish* •
- Adjustable mounting bracket •
- Complete mounting hardware for typical installations •
- L-bracket and Z-brackets available for easy mounting •
- Detachable faceplate •
- Lifetime limited warranty •

E-941SB-1K2PQ

Built-in dual-colored status LED and bond sensor to indicate locking status

Green	Door is closed and locked		
Red	Door is not closed and/or locked		
Off	Door in use / no power		

Bond sensor relay rated 1A@30VDC •

UL Listings

LIMITED

UL Designation		Country	1200	1K2PQ
UL294	Access Control System Units	USA	\checkmark	\checkmark
UL1034	Burglary Resistant Electric Lock	USA	\checkmark	
UL864	Fire Alarm Systems	USA	\checkmark	
UL10C	Positive Pressure Fire Test	USA	\checkmark	\checkmark
UL10B	Fire Test of Door Assemblies	USA	\checkmark	\checkmark
ULC-S104	Fire Test of Door Assemblies	Canada	\checkmark	\checkmark

*E-941SB-1200 and E-941SB-1K2PQ are also available with aluminum (US 28) finish (E-941SA-1200 and E-941SA-1K2PQ respectively). Contact SECO-LARM or visit www.seco-larm.com for details.

SECO-LARM[®] U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606 Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com

Copyright © 2023 SECO-LARM U.S.A, Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® **ENFORCER**® CRIMEBUSTER® CBA® **SLI**® **"Z**

PI_E-941SB-1xxxx_221117.docx

MOV

Surge

Protection

1.200-lb

Specifications

Model 1200 1K2PQ Holding force 1,200-lb (545kg) Operating voltage 12/24 VDC (selectable) Current draw 12VDC 500mA@12VDC draw 24VDC 250mA@24VDC 270mA@24VDC Operating temperature 32°~120° F (0°~49° C) Weight 11-lb (5kg) Bond sensor relay No SPDT 1A@30VDC						
Operating voltage 12/24 VDC (selectable) Current draw 12VDC 500mA@12VDC 24VDC 250mA@24VDC 270mA@24VDC Operating temperature 32°~120° F (0°~49° C) Weight 11-lb (5kg)	Model		1200	1K2PQ		
Current draw 12VDC 500mA@12VDC 24VDC 250mA@24VDC 270mA@24VDC Operating temperature 32°~120° F (0°~49° C) Weight 11-lb (5kg)	Holding force		1,200-lb (545kg)			
draw 24VDC 250mA@24VDC 270mA@24VDC Operating temperature 32°~120° F (0°~49° C) Weight 11-lb (5kg)	Operating voltage		12/24 VDC (selectable)			
Operating temperature 32°~120° F (0°~49° C) Weight 11-lb (5kg)		12VDC	500mA@12VDC			
Weight 11-lb (5kg)		24VDC	250mA@24VDC	270mA@24VDC		
	Operating temperature		32°~120° F (0°~49° C)			
Bond sensor relay No SPDT 1A@30VDC	Weight		11-lb (5kg)			
· · ·	Bond sensor relay		No	SPDT 1A@30VDC		
Status LED No Yes	Status LED		No	Yes		

CE Rolls





12/24

VDC

Access

Dimensions





Optional Accessories

