SECO-LARM®

600-lb Single-Door Electromagnetic Locks

E-941SB-600 Black, UL Listed

E-941SB-600PQ Black, with Bond Sensor and Status LED, UL listed

Features

- Multiple UL listings (see chart below)
- 12/24VDC Selectable
- MOV Surge protection
- Anodized aluminum housing with black finish*
- Detachable faceplate
- Adjustable mounting bracket
- Complete mounting hardware for typical installations
- L-bracket and Z-brackets available for easy mounting
- · Lifetime limited warranty

E -941SB-600PQ

 Built-in dual-colored status LED and bond sensor to indicate locking status

Green	Door is closed and locked
Red	Door is not closed and/or locked
Off	Door in use / no power

Bond sensor relay rated 1A@30VDC













Specifications

Model		600	600PQ	
Holding force		600-lb (272kg)		
Operating voltage		12/24 VDC (selectable)		
Current draw	12VDC	500mA@12VDC		
	24VDC	250mA@24VDC	270mA@24VDC	
Operating temperature		32°~120° F (0°~49° C)		
Weight		4-lb, 6-oz (2kg)		
Bond sensor relay		No	SPDT 1A@30VDC	
Status LED		No	Yes	

UL Listings


UL Designation		Country	600	600PQ
UL294	Access Control System Units	USA	✓	✓
UL1034	Burglary Resistant Electric Lock	USA	✓	
UL864	Fire Alarm Systems	USA	✓	
UL10C	Positive Pressure Fire Test	USA	✓	✓
UL10B	Fire Test of Door Assemblies	USA	✓	✓
ULC-S104	Fire Test of Door Assemblies	Canada	✓	✓

*E-941SB-600 and E-941SB-600PQ are also available with Aluminum (US 28) finish (E-941SA-600 and E-941SA-600PQ respectively). Contact SECO-LARM or visit www.seco-larm.com for details.


SECO-LARM® U.S.A., Inc.


16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 **Fax:** (949) 261-7326 **Website:** www.seco-larm.com **Email:** sales@seco-larm.com



Dimensions





Optional Accessories

For 600-lb Black Electromagnetic Locks



