



2MP License Plate Recognition IP Camera with Junction Box

O2BLP1M

7 -22mm motorized lens, white housing



Features

- Captures license plates up to 40mph*
 - Search and Match captured plates with recorder**
 - Captures up to 2MP @ 30fps (60fps in high frame rate mode)
 - Built-in standard PoE (IEEE 802.3af)
 - Smart IR with range up to 330' (depending on scene reflection)
 - Micro SD card slot up to 128GB (card not included)
 - Two-way audio support
 - Alarm input/output
 - ONVIF Profile T Compliant
 - IP67 weather resistance
 - Junction box included (works with NPT/BSP specifications)
- *in optimal conditions
**with compatible Speco NR series recorder



Capture and recognize vehicle plates



Included Junction Box



Camera Specifications

Image Sensor	1/2.8" Progressive Scan CMOS
Maximum Resolution	1920 x 1080 (2MP)
Field of View (H)	H: 44° ~ 17.6°; V: 25.6° ~ 10°; D: 49.7° ~ 20.2°
Minimum Illumination	0.005 lux@F1.6, AGC ON; 0 lux with IR
Day/Night	Smart IR
White Balance	Auto, Indoor, Outdoor, Manual
Electronic Shutter Speed	1/25s ~ 1/100000s
DNR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt: 0°~90°; Rotation: 0°~360°

Video Specifications

Main Resolution	1080P / 720P (1 ~ 30fps); HFR Mode: 1080P/720P (1~60fps)
Compression	H.265, H.264, MJPEG
Bitrate Control	VBR, CBR (64 Kbps ~ 6 Mbps)
Multiple Streaming	3 streams

Audio Specifications

Audio Compression	G.711A / G.711U
Audio in/out	2-way audio capable (additional equipment required)

Interfaces

Ethernet	10/100 Mbps RJ45
Power	DC jack
Microphone Input	3.5mm
Audio Out	3.5mm
Card Slot	MicroSD, up to 128GB (not included)
Alarm	1 CH alarm input; 1 CH alarm output
Reset	Yes

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPs, QoS
DDNS support	Speco DDNS (free of charge)
Security	Watermark, IP address filtering, video mask, heartbeat, password protection, non-photosensitive switch, image distortion correction
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth

System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Video tampering detection, scene change detection, license plate Recognition
Alarm Triggers	Motion detection, sensor alarm, SD card error, SD card full, IP address conflict, cable disconnection
Image Settings	Region of interest, Saturation, Brightness, Chroma, Contrast, Noise reduction

Client Specifications

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS; SecureGuard® CMS
Mobile	SecureGuard® Client; Speco Blue (iPhone® and Android™)
Other Platforms	Apple TV and Amazon Fire TV


Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	11.0W (max)
Operating Temperature	-40°F ~ 140°F
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	11.0" (L) x 3.94" (W) x 3.5" (H)
Unit Weight	2.29 lbs
Certifications	FCC, RoHS

Optional Accessories



Cameras Interfaces



ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/23/21

Apps available from the following:

