

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

Division 28	Electronic Safety and Security
Section 28 00 00	Electronic Safety and Security
Section 28 20 00	Electronic Surveillance
Section 28 23 00	Video Surveillance

Notes to Security System Specifiers - This A&E specification is written according to Construction Specifications Institute (CSI) 3-Part Format, based on MasterFormat™ (2016 Edition) and The Project Resource Manual – CSI Manual of Practice. CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. All trademarks are properties of their respective owners.

Part 1 General

1.1. Summary of Requirements

A. H6HRL Hybrid Digital Video Recorder (DVR)

1. The DVR shall collect 4 hybrid video channels and 2 IP video channels. Each hybrid channels shall be configurable for TVI or CVBS high definition cameras along with audio. The DVR shall digitize all channels of video and audio for the purpose of display, archive and requested distribution across the Ethernet network.

B. H16HRL Hybrid Digital Video Recorder (DVR)

2. The DVR shall collect 8 hybrid video channels and 8 IP video channels. Each hybrid channels shall be configurable for TVI or CVBS high definition cameras along with audio. The DVR shall digitize all channels of video and audio for the purpose of display, archive and requested distribution across the Ethernet network.

C. H24HRL Hybrid Digital Video Recorder (DVR)

3. The DVR shall collect 8 hybrid video channels, 8 IP video channels and 8 analog only video channels. Each hybrid channels shall be configurable for TVI or CVBS high definition cameras along with audio. The DVR shall digitize all channels of video and audio for the purpose of display, archive and requested distribution across the Ethernet network.

D. Related Requirements

1. Section 28 05 00 Common Work Results for Electronic Safety and Security
2. Section 28 05 19.11 Digital Video Recorders
3. Section 28 05 19.13 Hybrid Digital Video Recorders
4. Section 28 05 19.15 Network Video Recorders
5. Section 28 21 00 Surveillance Cameras
6. Section 28 21 13 IP Cameras
7. Section 28 23 13 Digital Video Recorders and Analog Recording Devices

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

1.2. References

A. Abbreviations

1. DDNS Dynamic Domain Name Server
2. DHCP Dynamic Host Configuration Protocol
3. DNS Domain Name Server
4. FTP File Transfer Protocol
5. GUI Graphical User Interface
6. HTTP Hypertext Transfer Protocol
7. HTTPS Secure HTTP
8. ICMP Internet Control Message Protocol
9. IGMP Internet Group Management Protocol
10. IP Internet Protocol
11. JPEG Joint Photographic Experts Group
12. MPEG Moving Pictures Experts Group
13. NAS Network Attached Storage
14. NIC Network Interface Controller
15. NTP Network Time Protocol over Ethernet
16. DVR Network Video Recorder
17. PoE Power over Ethernet
18. PPPoE Point-to-Point Protocol over Ethernet
19. P2P Peer-to-Peer
20. PTZ Pan Tilt Zoom
21. QoS Quality of Service
22. RTP Real-Time Transport Protocol
23. RTSP Real-Time Streaming Protocol
24. SD Card Secure Digital Flash Memory Card
25. SMTP Simple Mail Transfer Protocol
26. TCP Transmission Control Protocol
27. UDP User Datagram Protocol
28. UPnP Universal Plug and Play
29. VMS Video Management System
30. ESD Electrostatic discharge
31. MSIE Microsoft Internet Explorer
32. HDD Hard Disk Drive
33. EZ Easy
34. FF Fast Forward
35. FR Fast Reverse
36. DAS Direct Attached Storage
37. LAN Local Area Network
38. WAN Wide Area Network

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

1.3. Certifications, Standards and Ratings

A. Reference Standards

1. Networking
 - a. IEEE – 802.3 Ethernet Standards
2. Video
 - a. ISO/IEC 14496 Standards for MPEG-4
 - b. ITU-T Recommendation H.264/H.265

1.4. Submittals

A. Product Data

1. Provide manufacturer's datasheets in printed or electronic form.
2. Provide manufacturer's Installation and operating manuals/guides.
3. Provide manufacturer's warranty statement.

1.5. Qualifications

A. Manufacturer

1. Company specializing in manufacturing products at least ten years experience.

E. Supplier

1. Authorized distributor of specified manufacturer with at least 5 years.

F. Installer

1. Authorized installer of specified manufacturer with a least 5 years experience.

1.6. Delivery, Storage and Handling

A. Delivery

1. Deliver materials in original, unopened and undamaged packaging in accordance with manufacturer's instructions.

G. Storage

1. Store and guard materials from environmental and temperature conditions in accordance with manufacturer's instructions.

H. Handling

1. Handle and operate products and systems in accordance with manufacturer's instructions.

1.7. Warranty

A. Warranty Period

1. Manufacturer shall warranty DVR (except HDD) for a period of [5] years for the repair or replacement of defective equipment.
2. Manufacturer shall warranty HDD for a period of [3] years.

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

1.8. Certifications

B. Certification Types

1. CE (EMC/LVD)
2. FCC, Class A
3. RoHS

1.9. Tech Support

A. Support

1. Technical support shall be based in North America.
2. Technical support support shall be via email or toll-free phone number.
3. Technical support shall be available weekdays from 6 a.m. to 6 p.m. EST.

Part 2 Product

2.1. Manufacturer

A. Manufacturer

1. Speco Technologies
200 New Highway
Amityville, NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web Site: www.specotech.com

I. Product

1. HRL Series
2. Models:
 - a. H6HRL1TB, H6HRL2TB, H6HRL3TB, H6HRL4TB
H6HRL6TB, H6HRL8TB, H6HRL10TB, H6HRL12TB
H6HRL14TB
 - b. H16HRL2TB, H16HRL4TB, H16HRL6TB, H16HRL8TB
H16HRL12TB, H16HRL16TB, H16HRL20TB, H16HRL24TB
H16HRL28TB
 - c. H24HRL2TB, H24HRL4TB, H24HRL6TB, H24HRL8TB
H24HRL12TB, H24HRL16TB, H24HRL20TB, H24HRL24TB
H24HRL28TB

J. Product Description

1. A 4K H.265 Hybrid DVR with a combined 6, 16 or 24 channels of analog and IP video inputs.

2.2. Product Description

A. General

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

1. All equipment and materials used shall be standard components, regularly manufactured, regularly utilized in the manufacturer's system.
2. All systems and components shall have been thoroughly tested and proven in actual use.
3. All systems and components shall be provided with the availability of a toll free technical support phone number from the manufacturer. The phone number shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge.
4. All systems and components shall be provided with an explicit manufacturer warranty.

B. Description

1. DVR shall meet the requirements of business, government and general security surveillance applications.
2. DVR shall offer remote network connectivity to a properly specified PC computer that allows transmission of video and control data over the Ethernet network.
3. DVR shall offer a GUI incorporating video display areas, toolbars, control palettes and site/device trees.
4. DVR shall employ a high profile H.265 compression algorithm in the video digitizing scheme. Network IP cameras shall be the primary video input devices.
5. DVR shall offer simultaneously view live or playback while continuing to record and network transfer. The DVR shall provide full digital video and audio surveillance over a standard 100Base-T network.
6. DVR shall offer multiple continuously recorded digital video and audio channels onto a hard drive medium. Each channel of video data shall have the capability of being recorded, displayed, played back, archived and distributed simultaneously across the network.
7. The video shall also be capable of alarm notification based on motion via a built-in utility to configure motion detection of objects in the individual camera scenes. Each camera can be customized for motion area and sensitivity using grid blocks through the camera's setup tool. The motion events shall be transmitted to authorized users via an email notification utility.
8. The video shall also have selectable digital zoom on any camera in live view and playback mode. The video recording capability shall be fully scheduled using the built-in utility.
9. DVR shall also have full LAN, WAN and Internet connection capability. The DVR will require a broadband internet connection of a minimum 256 Mbps using either a static or dynamic type IP address. When using a dynamic IP address, DDNS shall be an available feature to track the IP address via a customized URL. The DVR supports TCP/IP and DHCP protocol.
10. DVR shall record user selectable resolution and frame rate set from within the GUI of the IP cameras.

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

11. DVR shall utilize a Digital Signature video authentication algorithm. It is a standard authentication that is based on a 128-bit message used to verify data integrity
12. DVR shall incorporate a series of EZ (easy) features used to simplify installation and configuration of the unit. These features shall include EZ-Setup, EZ-Network, EZ-Camera, EZ-Record, EZ-Copy and EZ-Search.
13. DVR shall support searching of recorded video from EZ Search, motion events, analytic events, date/time, museum, bookmarks, snapshots and logs.
14. DVR shall support the following playback functions: play, pause, FF, FR, and Digital Zoom.
15. On event, DVR shall trigger recording, control PTZ, Alarm Out, Pop-up alarm preview, send email, FTP, record snapshot, and activate buzzer and screen tips.
16. DVR shall offer a full multi-user authorization logon function. This function shall offer five levels of authorization based on Main Menu functions. There shall be an Administrator and User level offered. Anyone with a correct password shall log into the DVR.
17. DVR shall offer a GUI capable of complete recorder configuration and operation. Sub-features such as defined video display and control, component setup, recording setup, network setup and the use of dialog messages shall be provided in a comprehensive menu structure.
18. Operation of the system shall be facilitated by the use of a monitoring screen whereby a security operator can perform a full scope of surveillance duties using the front panel controls and indicators, the remote application software, the CMS software or a mouse.
19. DVR shall use a HDMI / VGA Main Monitor output for video display sequencing.
20. DVR shall be configurable for several foreign languages, other than English.
21. DVR shall support the use of PTZ type cameras either on an RS-485 bus using built-in protocols from several manufacturers or through the network of the PTZ IP camera.
22. The DVR shall support alarm in and relay out functions. The alarm events shall be transmitted to users via a built-in email utility.
23. DVR shall support a variety of different capacity hard drives.
24. The front panel shall contain a lights to indicate status of power on/off, HDD health and network connectivity.
25. DVR shall contain 2 x USB ports with one available on the front panel and one at the back of the unit.
26. DVR shall also be equipped for installation in a standard 19 in. (48.2 cm) rack shelf. The rear panel shall contain WAN network port (RJ45) to connect to internet, HDMI Main Monitor, VGA Main Monitor Output, Audio In/Out inputs, SATA, LAN (Network) port, and 2 USB connector.
27. DVR shall support exporting of video in AVI format with a stand-alone player.
28. DVR shall support exporting video to the following media types: DAS and NAS
29. DVR shall support and be equipped with an IR remote control.

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

30. DVR shall support and include a Multi-Client application for multi-DVR remote access.
31. DVR shall support bi-directional audio.
32. DVR shall meet or exceed the following design and performance specifications
33. DVR shall support multi-time zone and DST.
34. DVR shall support Smart Analytics to include abandoned object detection, missing object detection and line crossing.
35. DVR shall support S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD).
36. DVR shall support plug-n-play via Speco's free P2P service.
37. DVR shall support DDNS capability via Speco's free DDNS service.
38. DVR shall auto-discover Speco's and other ONVIF Profile S compliant IP cameras on the local network without needing to locate the cameras manually.
39. DVR shall incorporate an embedded Linux® operating system using a proprietary software application for control, management and display.

C. Electrical Specification

1. Power Input 12VDC
2. Power Supply DC12V/2A (H6HRL)
DC12V/4A (H16HRL, H24HRL)
3. Power Consumption ≤ 10W (H6HRL without HDD)
≤ 15W (H16HRL without HDD)
≤ 30W (H24HRL without HDD)

D. Environmental Specification

1. Operating Temperatures -4° to 122°F (-10° to 50°C)
2. Operating Humidity 10% to 90%, non-condensing

E. Environmental Specification

1. Dimension 11.8"W x 9.8"D x 1.8"H (300mm×248mm×45mm) (H6HRL)
15"W x 10.6"D x 1.8"H (300mm×268mm×45mm) (H16HRL, H24HRL)
2. Mounting Optional vented rack shelf

F. Mechanical Specification

1. System
 - a. Operating System: Embedded Linux
 - b. User Interface: Semi-transparent on-screen graphic overlays
2. Video
 - a. Analog Inputs 4 x BNC (H6HRL)
8 x BNC (H16HRL)
16 x BNC (H24HRL)

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

b. IP Inputs	4 (H6HRL) 8 (H16HRL, H24HRL) 16 x BNC (H24HRL)
c. Outputs	HDMI: 4Kx2K/1920x1080/1280x1024 VGA: 1920x1080/1280/x1024/1024x768 BNC: CVBS (used as the main or spot output)
d. Encoding	H.265
e. Resolutions	5MP/4MP/3MP/1080P/960P/720P 4K on 1 channel (H6HRL) 4K on all channels (H16HRL, H24HRL)
f. Frame Rate	4K @ 6fps/7fps 5MP@12fps/15Fps (PAL/NTSC) 1080P/720P/WD1@25fps/30fps (PAL/NTSC)
g. Pre-record	5 seconds
h. Post-record	10 minutes
i. Display Modes	1x1, 2x2, 3x3, 4x4, Custom
j. Outputs	1 x HDMI (4K), 1 x VGA
3. Audio	
a. Inputs	1 x RCA, 4/8 x PoE Ethernet (RJ45)
b. Outputs	1 x RCA
c. Codec	G.711A/G.711U
4. Record	
a. Record Stream	Dual Stream Recording
b. Resolution	4K/5MP/4MP/1080p/720p/WD1
c. Frame Rate	4K @ 6fps/7fps 5MP@12fps/15Fps (PAL/NTSC) 1080P/720P/WD1@25fps/30fps (PAL/NTSC)
d. Bit Rate	32-78Mbps
e. Mode	Manual/Schedule/Motion/Sensor/Intelligence
5. Playback	
a. Simultaneous Playback	4 Channel Max (H6HRL) 8 Channel Max (H16HRL) 16 Channel Max (H24HRL)
6. Network	
a. Interface	1 x 10/100Mbps (RJ45) (H6HRL) 1 x 10/100/1000Mbps (RJ45) (H6HRL, H24HRL)
b. Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, RTSP, ONVIF Profile S
7. PTZ	Remote control/remote client
8. Alarms	
a. Inputs	4 (H6HRL) 8 (H16HRL)

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

	16 (H24HRL)
b. Outputs	1 (H6HRL)
	2 (H16HRL)
	4 (H24HRL)
9. Auxiliary	
a. USB	2 x USB 2.0 ports
10. Front Panel	
a. Power Indicator	Power On, Blue
b. HDD Status	Recording, Blue
c. Network Indicator	Network access, Blue
11. Remote Control	Full remote control operation of PTZ
12. Remote Surveillance	
a. Web Viewer	MSIE
b. Control System	Speco Technologies SecureGuard
c. Mobile Devices	iOS, Android
13. External Storage	1 x SATA (14TB capacity) (H6HRL)
	2 x SATA (28TB capacity) (H16HRL, H24HRL)
	1 x eSATA (8TB capacity) (All Models)

Part 3 Execution

3.1 Examination

- A. Device shall be inspected for physical and cosmetic defects.
- B. Package box shall include device, power supply, mouse, remote control unit, installation and user guides on disk.

3.2 Preparation

- A. ESD-sensitive parts shall be properly protected against static buildup through the use of static shielding material.
- B. Package box shall contain adequate padding to prevent damage to device and parts during shipping.

3.3 Installation

- A. Device shall be installed in accordance with the manufacturers' installation guide provided.
- B. Device shall be installed by qualified service professionals.

A&E Specification

H6HRL/H16HRL/H24HRL Hybrid Digital Video Recorder

Speco Technologies
200 New Highway, Amityville NY 11701
Tel. 1-800-645-5516 Fax. 1-631-957-3880
Web site: www.specotech.com

- C. Device shall be installed in accordance with the National Electric Code or applicable local codes.
- D. Device shall be installed in locations which adequately supports the device's environmental and electrical requirements.

3.4 Field Quality Control

- A. Test for proper communication between device and supporting devices.
- B. Test for proper operation of device's system software and related software programs.
- C. Determine and report all problems to the manufacturers' customer service representatives.

3.5 Adjusting

- A. Make all necessary adjustments to the device and supporting devices to ensure the proper operation of the device.
- B. Make all necessary adjustments to the devices to satisfy end-user requirements.

3.6 Demonstration and Training

- A. Perform final inspection to validate and ensure proper functioning of device.